

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
23 December 2004 (23.12.2004)


PCT

(10) International Publication Number  
**WO 2004/111677 A1**

- (51) International Patent Classification<sup>7</sup>: G01S 5/00, H04Q 7/38 // 7/32, 7/22 (74) Agent: Leitzinger Oy; Tammasaarekatu 1, FI-00180 Helsinki (FI).
- (21) International Application Number: PCT/FI2004/050088 (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 10 June 2004 (10.06.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 20035094 12 June 2003 (12.06.2003) FI (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant (for all designated States except US): INDAGON OY [FI/FI]; Nuijamiestentie 5 A, FI-00400 Helsinki (FI).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): MIKKOLAINEN, Markus [FI/FI]; Kaivosrinteentie 2 U 161, FI-01610 Vantaa (FI). SÄRKKÄ, Simo [FI/FI]; Auringonkatu 8 G 67, FI-00210 Espoo (FI).

[Continued on next page]

(54) Title: A METHOD AND AN ARRANGEMENT FOR ESTIMATING THE POSITION OF A MOBILE TERMINAL WITH A PREDICTION METHOD, AND A MOBILE TERMINAL



(57) Abstract: A method an arrangement to reduce amount data to be sent in a tracking system of a mobile station (MTT) having a positioning device to obtain positioning data, and the mobile station (MTT) and the server (S) perform the following steps: the mobile station (MTT) sends its dynamic state parameters including at least the position and velocity, which are derived from the positioning measurements, to server (S), the mobile station (MTT) computes an error criterion based on said sent dynamic state and current dynamic state, which is derived from new positioning measurements, such that the error criterion is calculated based on at least sent and current velocities, the mobile station (MTT) sends a set of new dynamic state parameters, when the said error criterion is over a predefined limit.

WO 2004/111677 A1



**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*